

Belt and Disc Sander Safety and Operation Quiz Name _____ Date _____

1. Personal protective equipment which should be worn when operating the belt and disc sander are _____ and _____.
2. If the sanding disc rotates in a counterclockwise direction, hold stock being sanded _____ to _____ edge of the disc.
3. A serious _____ may happen to an operator who reaches across the rotating sanding disc.
4. If the disc is not operating smoothly, _____ the workshop personnel.
5. On most disc sanders the table can be adjusted _____ degrees.
6. Do not put so much _____ on the belt and disc so that the sander slows down.
7. Never leave the machine running while _____.
8. Use a _____ when a precise angle is needed on the stock.
9. Rest the workpiece _____ on the table.
10. When finished, ALWAYS clean up the _____, _____, and floor area

Match the number of each belt/disc sander part with the correct part name.

- _____ Belt Guard
- _____ Belt Sander Work Table
- _____ Belt Tensioning Lever
- _____ Belt Work Table Clamping Knob
- _____ Debris Duct
- _____ Disc Debris Duct
- _____ Disc Work Table Clamping Knob

- _____ Miter Gauge and Slot
- _____ On/Off Switch
- _____ Platen Housing
- _____ Sanding Belt
- _____ Sanding Disk
- _____ Tracking Adjustment

